



Illicit Discharge Detection & Elimination: A Citizen's Guide to Identifying & Preventing Stormwater Pollution



Stormwater & Illicit Discharge

During rainfall, storm drains convey water from impermeable surfaces such as city streets through a series of ditches and pipes to a natural outlet, such as a stream or river. The stormwater systems in place do not have the capability to clean or filter contaminants. Stormwater runoff is water from rain or melting snow that does not soak into the ground. It flows from rooftops, over paved areas, bare soil, and sloped lawns. Municipal storm sewer systems— storm drain inlets, pipes and ditches - collect stormwater runoff and convey it directly to local bodies of water.

During rainfall, storm drains convey water from impermeable surfaces such as city streets through a series of ditches and pipes to a natural outlet, such as a stream or river. The stormwater systems in place do not have the capability to clean or filter contaminants.

Ideally, the stormwater runoff is contaminant free. In reality, it picks up pollutants such as soil, animal waste, salt, pesticides, fertilizers, oil and grease, and debris and transports them to waterways where they are discharged with no treatment. This is stormwater pollution.

The "Illicit Discharge"

An illicit discharge is any discharge to a municipal storm sewer system that is not composed entirely of stormwater. Pollutants end up in storm sewer systems in a number of ways, many of which are easily preventable.



In some instances, companies and individuals have waste pipes tapped into stormwater pipes. In other cases, individuals use the storm drain inlets to dispose of various types of waste. Disposal of anything other than stormwater in storm sewers is illegal.

It is important to remember that municipal storm sewer systems are not set up to treat or process anything and exist solely to transport rain water to surrounding rivers, streams, and other bodies of water.



Western New York Stormwater Coalition

A partnership to protect water quality. A number of communities, government agencies and consultants in Western New York have joined together to develop a stormwater management program to protect our waterways and enhance our quality of life. The goal of the Coalition is to utilize regional collaboration to identify existing resources and develop programs to reduce the negative impacts of stormwater pollution.

The Coalition meets regularly to work collectively on developing and implementing a stormwater management program that complies with New York State's Phase II Stormwater regulations.

For information on your local stormwater program, Contact:

Margaret Bilquin
Niagara Falls Water Board
Sanitary Engineer
(716)299-7792
mbilquin@nfwb.org



Examples of Illicit Discharges:

- Sewage
- Pet Waste
- Laundry Wastewater
- Pool Water
- Automobile Wash water
- Improper Waste Oil Disposal
- Improper Disposal of Household / Commercial / Industrial Hazardous Waste
- Seepage from Septic Tanks
- Auto Leaks: Oil, Gas, Antifreeze, Brake Fluid, ATF
- Spills from Roadway Accidents

Signs of Illicit Discharge

The point in a storm sewer system where flow is discharged into a body of water is a storm sewer outfall. It may be a pipe or ditch. If the outfall is flowing when there has been no recent rainfall, this may indicate an illicit discharge. Visible sewage waste, foul odor, suds or other evidence of contamination, are indicators that an illicit discharge is contaminating the storm sewer system.

Remember to keep an eye out for inappropriate amounts of discharge from stormwater pipes, especially during dry weather. This could be a sign that there is a problem, and should be reported to the Niagara Falls Water Board.

To Report an Illicit Discharge, Contact:

Michael Eagler
Niagara Falls Water Board
Chief of Outside Infrastructure
(716)255-2039
meagler@nfwb.org

Things You Can do to Protect Water Quality:

- Never dump anything down storm drains
- Use fertilizers sparingly; sweep up any excess from driveways, sidewalks and roads
- Avoid pesticides; learn about Integrated Pest Management (IPM)
- Pick up after your pet
- Direct downspouts onto grassy areas away from paved surfaces
- Check vehicles for leaks
- Wash vehicles on grass instead of on the driveway, or take your car to the car wash
- Never drain pool water directly into a body of water. Always test the pool water first to ensure that pH levels are normal (6.5- 7.8) and chlorine levels are not detectable